



Halogen reflector

13528 15W 6V

Halogen reflector lamps – proven reliability Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data

• Product Data

| | |
|-------------------------------|----------------------------|
| Product number | 315044 |
| Full product name | 13528 15W GZ4 6V 1CT |
| Short product name | 13528 15W GZ4 6V 1CT/10X5F |
| Pieces per Sku | 1 |
| eop_pck_cfg | 10X5F |
| Skus/Case | 50 |
| Bar code on pack | 8711500409782 |
| Bar code on intermediate pack | 8711500419309 |
| Bar code on case | 8711500419293 |
| Logistics code(s) | 923883810104 |
| eop_net_weight_pp | 14.500 gr |

• General Characteristics

| | |
|----------------------|----------------|
| Philips Code | 13528 |
| ANSI Code | - |
| Cap-Base | GZ4 |
| Cap-Base Information | - |
| Bulb | R35 |
| Bulb Material | Quartz-UV Open |
| Reflector Finish | Smooth |
| Operating Position | s105 |
| Main Application | Projection |

Life to 50% failures 750 hr

• Electrical Characteristics

| | |
|---------|------|
| Watts | 15 W |
| Voltage | 6 V |

• Light Technical Characteristics

| | |
|-----------------------------|---------|
| Color Rendering Index | 100 Ra8 |
| Color Temperature Technical | 2900 K |

• Product Dimensions

| | |
|------------------|-------|
| Overall Length C | 40 mm |
| Diameter D | 35 mm |


• Luminaire Design Requirements

| | |
|---------------------|-------|
| Pinch Temperature | 350 C |
| Bulb Temperature | 900 C |
| Working Distance WD | 92 mm |

PHILIPS

sense and simplicity

Dimensional drawing



GZ4

| Product | C (Max) | D (Max) |
|------------------|---------|---------|
| 13528 15W GZ4 6V | 40 | 35 |



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, January 15
data subject to change