

Типы ламп	Номинальные значения			Мини-мальная продолжительность горения, ч	Размеры, мм			Тип цоколя по ГОСТ 28108-89	Номер рисунка		
	Напряжение, В	Мощность, Вт	Световой поток, лм		Диаметр колбы, D	Длина лампы, L	Высота светового центра, H				
										не более	
CM2,5-0,075	2,5	0,68 ¹⁾	—	100	4,3	15,0	—	1-M8-1			
CM3-0,2	3,0	0,2 ¹⁾	—			11,5	—	выводы			
CM3-0,6		0,6	2,0			200	15,0	—	1-M8-1		
CM6,3-1,4	6,3	1,4	3,0	4500	5,5	17,0	10,8±1,0	S6s/10			
CM6,3-1,6		1,6	8,2	140	11,0	30,0	—	B9s/14			
CM7,5-9	7,5	9,0	50,0	250	26,0	51,0	31,0±2,0	B15d/18			
CM13-5	13,0	5,0	40,0	125	20,0	37,0	23±2				
CM13-10		10,0	105,0		23,0	44,0	24±2				
CM13-15		15,0	180,0			26,0	51,0		32±2		
CM13-25		25,0	370,0								
CM15-0,6	15,0	0,6	1,0	1000	5,5	17,2	—	Ц6/8	РИС.		
CM26-5	26,0	5,0	40,0	125	20,0	37,0	23±2	B15d/18			
CM26-10		10,0	80,0	100					23,0	44,0	24±2
CM26-15		15,0	142,0		125	26,0	51,0				
CM26-25		25,0	362,0	50	36,0	57,0					
CM26-70		70,0	1000,0								
CM27-1,5	27,0	1,5	5,5	1000	5,5	17,0	—	S6s/10			
CM27-1,5-1						13,0		выводы			
CM27-18		18,0	220,0	150	15,4	33,0	18,5±1	B12/12			
CM28-0,05	28,0	0,05 ¹⁾	7,0	200	5,5	17,2	—	S6s/10			
CM28-0,05-1					5,8	17,5	—		выводы		
CM28-0,05-2					5,5	15,0		1-M10-1			
CM28-1,4		1,4	7,0	350 ²⁾	6,5	21,0	10±1,0	S6s/10			
CM28-1,4-1			8,0		7,5	17,2					
CM28-1,5		1,5	3,0	1000	6,5		20,0		специальн.	РИС.	
CM28-2		2,0 ¹⁾	—	100	6,9	7,2±1 ₂		BA7s/11			
CM28-2-1		2,0	8,0	350	9,0						
CM28-2,8		2,8	15,3	150	11,0	30,0		B9s/14			
CM28-2,8-1			15,0	350 ²⁾	11,5		15±1,5				
CM28-4,8		4,8	32,0	150	11,0						
CM28-4,8-1				350 ²⁾	11,5		17±1,5				
CM28-5		5,0	34,0	150	15,0	36,0	25	B15d/18			
CM28-5-1			37,0	125	20,0	37,0					
CM28-10		10,0	80,0	100					26,0	51,0	29±2
CM28-20		20,0	264,0								
CM28-20-1											

1) - сила тока, А

2) - минимальная наработка, ч