



Productbeschrijving: 64615 HLX
Product code: 4050300006796
Hoeveelheid: Vouwdoos (FS) bevat 1 Stuks (ST)

U vindt dit product in de eCatalogus:

http://catalog.myosram.com?~language=NL&~country=&it_p=4050300006796

Toepassingen	
Brandstand	p 90/15

Categorizations	
ANSI Code	EFN
LIF	A1/230

Algemene beschrijving	
Lampvoet	GZ6.35
Coating	dichroic

Bestelgegevens	
Product gewicht	28 g

Technisch - Elektrische gegevens	
Constructie vermogen	75 W
Constructie voltage	12 V
Brandspanning in volt	12 V
Nominaal vermogen	75 W
Nominale spanning	12 V

Technisch - Afmetingen	
Diameter	51.0 mm
Afstand a / LCL in mm	32 mm
Reflector diameter [PIM]	51 mm
Lengte	42.00 mm

Technisch - Levensduur	
Levensduur in uren	50 h

Technisch - Lichttechnische gegevens	
Focusmaat in mm	32.0 mm

Verpakkingseenheden				
Product code	Verpakkingstype en inhoud	Afmetingen in h x b x l	Bruto gewicht	Volume
4050300006796	Vouwdoos bevat 1 Stuks	46,000 mm x 46,000 mm x 58,000 mm	36,000 g (0,000 g)	0,123 Kub. dec.
4050300665528	Verzenddoos bevat 20 Stuks	107,000 mm x 121,000 mm x 238,000 mm	796,000 g (0,000 g)	3,162 Kub. dec.

Literature

For further technical information please refer to the following OSRAM brochure: Technology and applications, Low-voltage tungsten-halogen lamps and our cross-reference-list "Halogen lamps, low and medium voltage for entertainment, technical and medical applications"