



product details

L 22W/640 C G10Q FLH1

Product description: L 22W/640 C G10Q FLH1
EAN/ Product: 4050300207421
Quantity: Sleeves (FLH) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300207421

General Description	
Energy Label - EEI	B
Base (standard designation)	G10q
Recycling	yes

Technical - Electrical Data	
Nominal wattage (packaging)	22 W

Technical - Geometries	
Tube diameter	29 mm
Length	216 mm

Technical - Life	
Service life	6000 h
Lifespan	7500 h ¹⁾

Technical - Light Technical Data	
Colour temperature	4000 K
Colour rendering group	2B
Colour rendering index Ra	60 ... 69
Light colour	640
Luminous flux	1100 lm

Packaging units				
EAN	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300207421	Sleeves contains 1 Piece	212,000 mm x 38,000 mm x 225,000 mm	196,000 g (0,000 g)	1,813 Cubic dec.
4050300207438	Shipping carton box contains 12 Piece	238,000 mm x 227,000 mm x 450,000 mm	2.747,000 g (0,000 g)	24,312 Cubic dec.

system overview											
operation of lamp with	Length in mm	Number of lighting outlet	Length in mm	Width in mm	Height in mm	System power consumption in W (ECG)	System power consumption in W (CCG)	System power consumption in W (LLB)	Luminous flux with ECG in lumen	Luminous flux in lumen (CCG)	Power factor
QT 1x24/230-240	216 mm	1	237 mm	30 mm	30 mm	23 W	34 W	32 W	1000 lm	1000 lm	1
QT-ECO 1X18-24/220-240 S	216 mm	1	80 mm	40 mm	22 mm	20 W	54 W	52 W	1100 lm	1000 lm	1.1
QT-ECO 1X18-24/220-240 L	216 mm	1	150 mm	22 mm	22 mm	20 W	54 W	52 W	1100 lm	1000 lm	1.1
QTI DALI 1X14/24 DIM	216 mm	1	360 mm	30 mm	21 mm						
QTI 1X14/24 DIM	216 mm	1	360 mm	30 mm	21 mm						
QT-M 1X26-42/230-240	216 mm	1	103 mm	67 mm	31 mm	26 W	34 W	32 W	1000 lm	1000 lm	1
QT-M 2x26-32/230-240	216 mm	2	123 mm	79 mm	33 mm	40 W	54 W	52 W	2 * 1000 lm	2 * 1000 lm	1



product details

L 22W/640 C G10Q FLH1

¹⁾ With preheat ECG