

OSRAM



Electric Automation
Automation specialists

Артикул: DECOSTAR 51S 50 W 12 V 36°
GU5.3
код: 4050300272795

HAL DECOSTAR 51S Standard 44870
WFL 50W 12V GU5,3

Покупка от Electric Automation Network



DECOSTAR 51S 50 W 12 V 36° GU5.3

Electrical data

Nominal wattage	50.00 Вт
Номинальная voltage	12.0 V
Rated wattage	50.00 Вт
Power Factor (коэффициент мощности λ	1.00

Photometrical data

Nominal useful luminous flux 90°	680 lm
Luminous intensity	1450 cd
Rated color temperature	2950 K
Light цвет (designation)	Warm White
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.75
Rated useful luminous flux 90°	680 lm
Rated peak intensity	1450 cd

Light technical data

Beam angle	36 °
------------	------

Номинальный beam angle	36 °
Starting time	0.0 s
Warm-up time (60 %)	0.00 s
Rated beam angle (half peak value)	36.00 °

Dimensions & weight

Diameter	51.0 мм
Length	46.0 мм
Overall length	46.0 мм
Outer bulb	MR51
Maximum diameter	51.0 мм

Lifespan

Номинальный lamp life time	2000 ч
Rated lamp life time	2000 ч
Number of switching cycles	100000

Atd>

Base (standard designation)	GU5.3
Mercury content	0.0 мг
Mercury-free	Yes

Capabilities

Burning position	Any
Dimmable	Yes

Certificates & standards

Energy efficiency class	C
Energy consumption	54 kWh/1000h

Country specific categorizations

ILCOS	HRGS//UB-50-12-GU5.3-51/36
-------	----------------------------