



product details

64440 50W 12V GY6,35 FS1



Product description: 64440 50W 12V GY6,35 FS1
Product code: 4050300324432
Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300324432

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
ILCOS	HSGST/C/UB-50-12-GY6,35-12/30

General Description	
Base (standard designation)	GY6.35
Filament setting	Transversal
Mercury-free	Yes
Rated lamp mercury content	0.0 mg

Technical - Electrical Data	
Nominal wattage (packaging)	50 W
Construction wattage	50 W
Nominal voltage	12 V
Rated number of switching cycles	1000000
Rated power factor λ	1.00

Technical - Geometries	
Overall length	44.00 mm
Contact spacing	6.35 mm
Diameter	12unece.unit.MMT
Length	44.00 mm
Light centre length (LCL)	30 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Rated color rendering index (Ra)	100
Luminous flux	910 lm
Nominal luminous flux	720 lm
Rated luminous flux	720 lm
Lumen main.fact.at end of nom.life time	0.80
Color temperature	3000 K
Rated color temperature	3000 K
Color rendering index Ra	100
Rated warm-up time (60%)	0 s
Rated starting time	0.0 s



product details

64440 50W 12V GY6,35 FS1

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300324432	Folding carton box contains 1 Piece	37,000 mm x 23,000 mm x 80,000 mm	25,375 g (0,000 g)	0,040 Cubic dec.
4050300942216	Shipping carton box contains 40 Piece	121,000 mm x 138,000 mm x 126,000 mm	273,286 g (0,000 g)	1,899 Cubic dec.

Lighting solutions that are unlike anything else - that's HALOSTAR from OSRAM. Open halogen lighting systems and unshielded luminaires are no longer a problem. These decorative reliable point light sources bring rooms to life. It is now possible to design, create and present in the finest detail.

- Brilliant accent light
- Incredibly small dimensions for revolutionary new luminaire designs
- Approved for use in open luminaires to IEC 60598-1
- Average life: 2,000 h
- Dimmable
- Ra=100
- Color temperature: 10 W/20 W - 2,800 K; 35 W - 2,900 K; 50 W - 3,000 K
- Base: G4, GY6.35
- UV filter