

Technical Data Sheet

LIGHTTECH MEDSUN THERAPY VITAMIN D 36W T8 TEFLON

Art. Nr.: N/A




Main application:

Medical (UVB phototherapy)

Dimensions

Lamp Length Nominal:	1200 mm
"A" Base Face to Base Face min.:	1197,0 mm
"A" Base Face to Base Face max.:	1199,4 mm
"B" Base Face to Pin min.:	1204,1 mm
"B" Base Face to Pin max.:	1206,5 mm
"D" Diameter Nominal:	26 mm
Base:	G13 Bi-Pin
Reflector angle:	0 °




Electrical Data (nominal values)¹⁾

Lamp Wattage	36 W
Lamp Current	0,36 A
Lamp Voltage	130 V
Compensation	4 µF
Recommended Ballast	40 W

Physical Data (nominal values)¹⁾

UVB Radiant Flux	0,18 W
B/A Ratio (UVB:280-315 nm)	40,0 %
E_{er} (250-400 nm)	25 mW/m ²
E_{er} (320-400 nm)	0,35 mW/m ²
E_{er} (250-320 nm)	25,0 mW/m ²
NMSC Ratio (≤ 320 nm / > 320 nm)	86,0

Relative Spectral Radiant Flux



LightTech Lamp Technology Ltd.

H-2120 Dunakeszi Hegyujáró u.1.

Tel: +36 / 27/541-800

Fax: +36 / 27/390-099

info@lighttech.hu

www.lighttech.hu

1) Single lamp, aged for 5h

Measuring distance: 0,25m

Measured under conditions of optimum UV irradiance

DANGER - UV radiation! Only for medical use! The lamp must be used under the supervision of a dermatologist.

Lamps have an outer sleeve made from FEP. This is a special option which ensures that all the components of lamp are retained in the outer sleeve in the case of accidental breakage.

Subject to modification.